## **Amendments to the Claims**

This listing of claims will replace all prior versions, and listings, of claims in this Application.

## **Listing of Claims:**

Claims 1-17. (Canceled)

Claim 18. (Currently Amended) A method for forming a trim panel consisting of:

a. supplying a cloth having a backside;

b. coating said backside with a liquid polyurethane dispersion dispersed in water to

form a relatively smooth gauged backing layer thickness of about 2.6 – 51.3 mm and drying

evaporating the water from said backing layer;

c. forming a molded plastic substrate using the injection molding process on said

backing layer wherein said backing layer does not allow strike-through of the cloth by said

injection molded plastic substrate; and

d. incorporating said cloth including said molded plastic substrate into a vehicle as a

trim cover-wherein said trim cover has an air flow permeability of at least 38 ft<sup>3</sup>/min/ft<sup>2</sup>.

Claims 19-20. (Canceled)

Claim 21. (Previously Presented) The method of claim 18, wherein the cloth is woven.

Appln. No. 10/629,979

Amndt F filed w/RCE dated Nov. 28, 2007

Reply to Final Office Action of Aug. 28, 2007

Claim 22. (Previously Presented) The method of claim 18, wherein the cloth is knit.

Claim 23. (Previously Presented) The method of claim 18, wherein the polyurethane

dispersion is in the form of a foam layer having a density in the range of 0.016 to 0.32

grams/cubic centimeter.

Claim 24. (Canceled).

Claim 25. (Previously Presented) The method of claim 18, wherein the cloth has a basis

weight of between 100 - 950 grams/square meter.